MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

| AIRPORT: | BIG TIMBER (6S0) | AIRPORT REFERENCE CODE: | B-I (SM) |
|----------|------------------|-------------------------|----------|
| CITY: | BIG TIMBER | APPROACH TYPE: | VISUAL |
| CONTACT: | JUSTIN FERGUSON | DATE INVENTORIED: | 9-15-95 |
| PHONE #: | 932-4389 | INSPECTED BY: | RSD |

| | REQUIRED | ACTUAL | ALP | CONFORM |
|--|-------------------------|-----------|---------|----------|
| RUNWAY 6/24 INVENTORY | | | | |
| DISTANCE TO: | | | | |
| HOLD LINES FROM CENTERLINE: | 125' | 125' | | ✓ |
| PARALLEL TAXIWAY FROM CENTERLINE: | 150' | 205' | | ✓ |
| AIRCRAFT PARKING FROM CENTERLINE: | 125' | 262' (1) | | ✓ |
| RUNWAY WIDTH: | 60' | 75' | | ✓ |
| RUNWAY LENGTH: | 5,870' (2) | | 4,650' | 75% |
| RUNWAY SAFETY AREA (RSA) WIDTH: | 120' | OK | | ✓ |
| RUNWAY OBJECT FREE AREA (OFA) WIDTH: | 250' | (3) | | NO |
| PRIMARY / TRANSITION SURFACE PENETRATIONS: | 250' W & 7:1 | (4) | | NO |
| LONGITUDINAL GRADE - SITE DIST. PROBLEMS: | | OK | | ✓ |
| OBSTACLE FREE ZONE ANALYSIS: | 250' WIDE x 200' BEYOND | | | (3) |
| PAVEMENT EDGE LIP HEIGHT (MIN AND MAX): | 1.5" - 3" | FLUSH | | NO |
| PAVEMENT MARKING TYPE: | BASIC | BASIC (5) | | NO |
| PAVEMENT MARKING CONDITION: | | POOR | | N/A |
| | | | | |
| RUNWAY 6 END INVENTORY | | | | |
| SAFETY AREA (RSA) BEYOND RUNWAY END: | 240' | ОК | | / |
| OBJECT FREE AREA (OFA) BEYOND RUNWAY END: | 240' | OK | | / |
| APPROACH OBSTRUCTIONS: | 20:1 | NONE | | / |
| RUNWAY END ELEVATION: | 20.1 | NONL | 4,482.0 | N/A |
| NOWWAT END LEEVATION. | | | 7,702.0 | IN//A |
| | | | | |
| RUNWAY END INVENTORY | | | | |
| SAFETY AREA (RSA) BEYOND RUNWAY END: | 240' | OK | | ✓ |
| OBJECT FREE AREA (OFA) BEYOND RUNWAY END: | 240' | OK | | ✓ |
| APPROACH OBSTRUCTIONS: | 20:1 | NONE | | ✓ |
| RUNWAY END ELEVATION: | | | 4,454.7 | N/A |
| | | | | |
| RUNWAY LIGHTING INVENTORY | | | | |
| DISTANCE FROM PAVEMENT EDGE: | 10' | 10' | | / |
| MAXIMUM DISTANCE BETWEEN LIGHTS: | 200' | OK | | / |
| TYPE: | MIRL HUGHEY & PHILLIPS | | | N/A |
| CONDITION: | WIINETIOOTIET | FAIR | | N/A |
| COLOR: | WHITE | WHITE | | √ |
| | ****** | VVIII1 | | • |
| THRESHOLD 6 | | | | |
| DISTANCE FROM PAVEMENT EDGE: | 10' | 5' (6) | | OK |
| MAXIMUM DISTANCE BETWEEN LIGHTS: | 10' | 10' | | ✓ |
| COLOR: | RED/GREEN | RED/GREEN | | ✓ |
| THRESHOLD 24 | | | | |
| DISTANCE FROM PAVEMENT EDGE: | 10' | <10' (6) | | OK |
| MAXIMUM DISTANCE BETWEEN LIGHTS: | 10' | 10' | | √ |
| COLOR: | RED/GREEN | RED/GREEN | | ✓ |

COMMENTS:

- (1) DISTANCE IS TO FIRST TIE DOWN ANCHOR
- (2) R/W LENGTH OF 4,260' FOR 75%, 5,600' FOR 95% AND 5,870' FOR 100% COVERAGE; ALP ULT OF 5,500' SHOWN
- (3) 55 GAL BURN BARREL 102' FROM CL, VARIOUS PIECES OF WINDBLOWN METAL SIDING LYING ABOUT, SOME IN OFA
- (4) TWO ANTENNA PENETRATE TRANSITIONAL SURFACE, BOTH MOUNTED ON BUILDINGS ONE AT 26% THE OTHER AT 17%
- (5) 6" WIDE, NON STANDARD SPACING CENTERLINE PAINT, & NOT TO STRAIGHT
- (6) THRESHOLD LIGHTS LESS THAN 10' FROM PAVEMENT BUT BOTH ENDS ARE 30' FROM RUNWAY END NUMBER PAINT

MONTANA STATE AVIATION SYSTEM PLAN 1995 UPDATE FIELD INSPECTION FORM

| | FIELD INSPE | CTION FORM | 1 | | | | |
|---|-------------------------------|---|-------------------------|-------------|---------|----------|--|
| AIRPORT: | BIG TIMBER (6S0) | | AIRPORT REFERENCE CODE: | | | B-I (SM) | |
| CITY: | | | APPROACH TYPE: | | | VISUAL | |
| CONTACT: | | DATE INVENTORIED: | | | 9-15-95 | | |
| PHONE #: | 932-4389 | | INS | SPECTED BY: | | RSD | |
| | | | | | | | |
| TAXIWAY INVENTO |)RY | REQUIRED | | ACTUAL | ALP | CONFORM | |
| TAXIWAY WIDTH: | | 25' | | 25' & 30' | | ✓ | |
| TAXIWAY SAFETY AREA WIDTH: | | 49 | | OK | | / | |
| TAXIWAY OBJECT FREE AREA WIDTH: | | 89 | | OK OK | | / | |
| DIST. FROM CENTERLINE TO FIXED OR MOVEABLE OBJ. PAVEMENT EDGE LIP HEIGHT (MIN AND MAX): | | 44.5 1.5" - 3" | | FLUSH | | √ NO | |
| PAVEMENT MARKING TYPE: | | 1.5 - 5 | | YELLOW | | / | |
| PAVEMENT MARKING CONDITION: | | | | FAIR | | N/A | |
| TAXIWAY LIGHTING INVENTORY | | | | DIDN'T | | N/A | |
| DISTANCE FROM | _ | 10' | | RECORD | | | |
| MAXIMUM DISTANCE BETWEEN LIGHTS: TYPE: | | 200' | | | | | |
| CONDITION: | | | | | | | |
| COLOR: | | BLUE | | | | | |
| | | | | | | | |
| MISCELLANEOUS | | | | | | | |
| TYPE OF BEACON: | | MOUNTED METAL TOWER NORHT OF APRON AREA | | | | | |
| SIZE OF BEACON: | | DIDN'T RECORD | | | | | |
| OTHER LIGHTING AIDS (VASI,PAPI,REIL): | | NONE | | | | | |
| WINDCONE (CONDITION & COMPLIANCE): | | SOUTH OF RW ~500', LIGHTED FROM GROUND, ~25', FAIR COND | | | | | |
| SEGMENTED CIRCLE (CONDITION & COMPLIANCE): | | TIRES PAINTEI | | | | | |
| WINDCONE (CONI | DITION & COMPLIANCE): | | | | | | |
| SEGMENTED CIRC | CLE (CONDITION & COMPLIANCE): | | | | | | |
| FENCING: | | GOOD | | | | | |
| SIGNS: (TYPE, CO | NDITION, PLACEMENT) | NONE | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| COMMENTS: | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |